Brivo Recessed Smart Reader
Installation Guide

(EN) Included Parts:

Reader and mounting Wall Plate

- #6 Machine Screws – QTY 2 (Wall Plate Screws)
- #6 Self Tapping Screws – QTY 2 (Wall Plate Screws)
- #6-32 Phillips Screw (Security Screw)
- #6-32 Pin-in-Torx Screw (Security Screw)

Tools Needed (Not Supplied):

- Phillips Screwdriver
- 1" (25mm), 1/8" (3.175mm) drill bits
- T6 Security Torx Bit (optional for increased tamper detection)

(FR) Pièces incluses:

Lecteur et plaque murale de montage

- #6 vis mécaniques – QTE 2 (Vis de plaque murale)
- #6 vis autotaraudeuses – QTE 2 (Vis de plaque murale)
- #6-32 Vis Phillips (Vis de sécurité)
- #6-32 Vis Pin-in-Torx (Vis de sécurité)


Outils nécessaires (non fournis) :

- Tournevis Phillips Forets de
- 1" (25mm), 1/8" (3.175mm) Embout Torx de sécurité
- T6 (optionnel pour une détection accrue des manipulations)

Taraud

Wiring is done with the terminal blocks. The terminal blocks are identical for both the US and EU versions.

Pin	Color	Description
1 - 1	Red	5-24 VDC
1 - 2	Black	Ground
1 - 3	White	Wiegand W1/OSDP RS485B
1 - 4	Green	Wiegand W0/OSDP RS485A




Pin	Color	Description
2 - 1	Orange	Red LED Control
2 - 2	Brown	Tamper Out
2 - 3	Yellow	Buzzer Control
2 - 4	Blue	Green LED Control

(EN) All wiring methods used shall be in accordance with the National Electrical Code, ANSI/NFPA 70 and local codes. The reader is to be installed in accordance with Canadian Electrical Code (CE Code) CSA C22.1. Readers must be powered by a compatible UL Listed, limited power source, access control panel rated 5-24VDC.

(FR) Toutes les méthodes de câblage utilisées doivent être conformes au Code National de l'Électricité, ANSI/NFPA 70 et aux codes locaux. Le lecteur doit être installé conformément au Code canadien de l'électricité (CCE), CSA C22.1. Les lecteurs doivent être alimentés par un panneau de contrôle d'accès compatible, homologué UL, à puissance limitée, et évalué pour 5-24VCC.

1



Connect the Recessed Reader (attached to the mounting plate) to the US style junction box. The mounting plate must be mounted with two of the provided screws as shown.

2



The wall plate is then attached to the reader mounting plate from the top. Swinging the wall plate down into place, the bottom security screw should be torqued to 8 inch-lbs.

7700 Old Georgetown Road, Suite 300, Bethesda, MD, 20814
3001 Bee Caves Road, Austin, TX, 78746

Recessed Reader (Brivo Part Numbers) B-BSPR-US-B,B-BSPR-EU-B, B-BSR-US-B, B-BSR-EU-B	
Tri-Tech Radios	125 kHz Prox, 13.56 MHz NFC, and BLE Credentials and Configure App
Dual-Tech Radios	13.56 MHz NFC, and BLE Configure App
Voltage	5 - 24 VDC
Max Current @5V, 12V, 24V	Recessed US: 150mA / 75mA / 45mA | Recessed EU: 150mA / 75mA / 45mA
Temperature	Temperature rating per UL294/ULC60839-11-1: -40C to 66C
Humidity	Humidity rating per UL294/ULC60839-11-1: 32C at 95% humidity
Cable Length	Wiegand: 500 feet with 18 AWG Wiring OSDP RS485 (powered at 12VDC): 1000 feet with 22 AWG Twisted Pair

Startup Sequence		
On power up, the Brivo Recessed Smart Readers provide a LED and beeper sequence to provide information about the reader type and its communication mode. The first sequence describes the RF Technologies		
Tri-Tech (HF + Prox + BLE)	**Dual-Tech** (HF + BLE)	
3 Green LED Flashes	2 Green LED Flashes	
The second sequence indicates the Wiegand / OSDP Mode		
Wiegand Only	**OSDP Only**	**Auto-Detect**
Beep and Blink Red LED Once	Beep and Blink Green LED 2 Times	Beep and Blink Green LED 4 times

Wiegand Keypad Mode Setup		
Within one minute of reader reset, enter the keypad config code: *88889999.Thereader beeps three times, LED flashes green for each beep. Within 2 seconds of entering the keypad config code, press the corresponding key code below for the desired format. The reader then beeps three times, LED flashes green for each beep.		
4-Bit Format	8-Bit Format	26-Bit Format
***4**	***8**	**#077**

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
• Reorient or relocate the receiving antenna. Increase the separation between the equipment and receiver.
• Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. For MS1 rating, equipment should not be installed above 2 meters.

Consult the dealer or an experienced radio/TV technician for help. This telecommunication equipment conforms to NTC technical requirement This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions: 1.This device may not cause interference. 2. This device must accept any interference, including interference that may cause undesired operation of the device.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: 1. L'appareil ne doit pas produire de brouillage. 2. L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement. Pour la classification MS1, l'équipement ne doit pas être installé à plus de 2 mètres.

Warning: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer. For more information, go to P65Warnings.ca.gov.

Performance Levels:
Destructive Attack: I
Line Security: I
Endurance: IV (125 kHz, 13.56 MHz), I (BLE[1])
Standby Power: I
Shall be powered by a UL 294 or ULC-60839-11-1 Listed control panel
CAN / ULC 60839-11-1: Outdoor Rating Grade 1

Approvals:
EN302291, EN301489, EN300330, IP65, UL294

Secure Mode Compatibility
Please note that for security, our updated Brivo Smart Readers, both full-size and recessed, can no longer be swapped between control panels when configured in secure mode and keyed with a panel. If a reader needs to be moved to a different panel after establishing a secure connection, it must first be reset to Auto-Detect mode using the WaveLynx Configure app.

- **Configuration Token:** To restore the reader to the Auto-Detect configuration, use the following token in the WaveLynx Configure app:
  - **Auto-Detect Configuration Token**: c-xRsEjkZL

Manufacturer Model: AX-R5

[1] BLE Android and/or iOS versions have not been evaluated against UL294 & ULC60839-11-1

© 2026 Brivo, Inc. All rights reserved.